

NICEA MINI

Recess walk-over spotlights




KELVIN	CRI	REAL OUTPUT	ENERGY CLASS
2700	90	~ 40	G
3000	90	~ 40	G
4000	80	~ 50	G

2006/95/CE -- 2002 /95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-2
 -- EN 60598 2-13 -- EN 62471 -- EN 62031



Nicea Mini 2.1 W



Code: **3167**

SHAPE	FINISH	COLOUR	OPTICALS
Round	Grey ANODIZED Black ANODIZED Inox AISI 316 STEEL	4000 K 3000 K 2700 K Red Green Blue	Side

ACCESSORIES

30500012	Outer casing
330010000	(Vin 220/240 Vac) 700 mA - 7.7 W - IP20
330009700	(Vin 220/240 Vac) 700 mA - 10 W - IP20
330009500	(Vin 220/240 Vac) 700 mA - 14 W - IP67
330009900	(Vin 220/240 Vac) 700 mA - 30 W (min 14 W) - IP67
330007800	(Vin 220/240 Vac) 700 mA - 20 W (min 7W)
330007200	(Vin 220/240 Vac) 700 mA - 28 W (min 2 W) - Dimmer Push, 0-10, 1-10, DALI
307500010	Neoprene cable 2x0.5
307500020	IP68 connector
307500027	NO-W system, 2 pole cable interrupting
307500044	NOW System with 24 vdc - 700 mA converter

Description

IP66 drive-on recessed spotlights, wattages 2.1 W per emission. Installation with counter casing on masonry. Available with round aluminium or steel flange, anodised aluminium body. Finish obtained by anodising. Available in colour temperatures 2700 K - CRI 90 / 3000 K - CRI 90 / 4000 K - CRI 80, MacAdam Step 2. All-round optics (lateral emission) with 100° emission. Supplied with 1 m of 2x0.5 mm section neoprene cable. Durability L80 B20 at 100.000h Ta (ambient temperature) 25° C. Version with ballast to be ordered separately available.