

KARAH V.

Applique / Wall lamp




KELVIN	CRI	REAL OUTPUT	ENERGY CLASS
2700	90	~ 430/430	F
3000	90	~ 500/500	E
4000	80	~ 520/520	E

2006/95/CE -- 2002 /95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1 -- EN 62471 -- EN 62031



Karah V. D/I 9.6 W



W
9,6

Code: **3404**

SHAPE	FINISH	COLOUR	OPTICALS	COLOUR UP	OPTICALS UP
Square	Anthracite ■ RAL 7016	4000 K	20°	4000 K	20°
	White □ RAL 9010	3000 K	40°	3000 K	40°
	Grey ■ RAL 7042	2700 K	60°	2700 K	60°
	Black ■ RAL 9005		Diffused		Diffused
	Cor-ten ■ SX350F M				

ACCESSORIES

330008800	(Vin 220/240 Vac) 500 mA - 10 W
330002200	(Vin 220/240 Vac) 500 mA - 22 W (min 6 W)
330006800	(Vin 220/240 Vac) 500 mA - 14 W - IP67
330007200	(Vin 220/240 Vac) 500 mA - 23 W (min 4.5 W) - Dimmer Push, 0-10, 1-10, DALI
330009800	(Vin 220/240 Vac) 500 mA - 28 W (min 14 W) - IP67

Description

Outdoor wall lamp IP65 direct light with wattage 4.8 W per emission. Installation with bracket without visible screws. Rectangular shapes. Aluminium body, powder-coated finish. Available in colour temperatures 2700 K- GRI 90 / 3000 K- GRI 90 / 4000 K- GRI 80, MacAdam Step 2. Optics 20° /40° /60°. Diffuse light emission. Service life L80 B20 at 100.000h Ta (ambient temperature) 25° C. Power supply must be ordered separately.